



## B Series

### Description:


Complete high quality acrylic polyurethane basecoat product range. Plain or metallic colors, based on 56 base colors including 15 Pearlescent and iridescent colors and 6 xiralllic. High pigmented system, economy on the quantity of paint ready for use, greater coverage, time saving in application because 2 coats are sufficient. Minimal waiting time for the application of the top coat. The basecoat system can be used sometimes with T Series in quantities exceeding 25%.

### Surface Preparation:


Old paint well sanded and surfaces well primed and prepared.

### Suitable Substrates:

- Existing Finishes except TPA
- “**Turbo**” 1 K or 2 K primers
- OEM Primer or EDP, sanded
- “**Turbo**” Polyester Putties
- Bare metal substrates must be pre-primed with wash primer **P97**



75% “Turbo” thinners  
100% “Turbo” thinner for pearlescent 3 stage colors



18-19 sec / DIN 4 mm / 20 °C (68 °F)




Compliant 1.3 – 1.4 mm  
2.0 – 2.5 bar inlet pressure  
HVLP 1.3 – 1.4 mim; 0.7 bars at the air-cap  
8 – 12 microns per coat



5 min. between coats. For metallic colors, a drop coat is recommended



## B Series



Wait until fully matt before applying top coat.

---

**Flash Point:** 23°C (73.4 °F)

---

**Specific Gravity:** 0.94 – 1.16 kg/cm<sup>3</sup> (7.82 – 9.66 lbs/gal)

---

**Solids Content:** 21.2 – 39.0 % by weight

---

**Coverage:** 8 – 10 m<sup>2</sup>/l at 25 micron dry thickness

---

**SDS:** See the safety data sheet